



Rating	3A 125VAC	Electrical Life	10,000 cycles
Contact Resistance	100mΩ Max	Mechanical Life	1000,000 cycles
Insulation Resistance	>100MΩ DC500V	Ambient Temper. Used	-25℃ to +85℃
Withstand Voltage	AC500V 1min.	Ambient Humidity Used	≤85% at +40℃
Soldering Temper.	235±5℃ 5s	Operating Force	90 ±30gf max

KW2-3 3A125VAC $\mu$   
1.5A 250VAC $\mu$

C NO NC



6	触点	1	银镍合金	
5	按钮	1	PBT 阻燃料	
4	压簧	1	SUS301	
3	弹片	1	C17200	
2	盖片	1	PBT 阻燃料	
1	底座	1	PBT 阻燃料	
序号	零件名称	数量	材质	备注

东莞市欧高电子有限公司  
DONGGUAN AUGO ELECTRONICS CO., LTD.

微动开关  
KW2-3-68P-90-5

制图 DRAWN																			
设计 DESIGN																			
审核 CHECKED						比例 SCALE	4:1	名称 TITLE	微动开关										
批准 APPROVE						张数 SHEET	1/1	序号 P/N NO.	KW2-3-68P-90-5										
公差 TOLERANCE						单位 UNIT	mm	规格 P/N NO.											
						角度 ANGLES	±2.0°	规格 SIZE	A4	画法 P R O J.		工程 ENG DRAW							

版本 REV.	ECN 编号 ECN NO.	日期 DATE	定义内容 DEFINITION	修改 DRAW	批准 APPROVE
------------	-------------------	------------	--------------------	------------	---------------